

Dimensionen

Durchmesser aussen	Durchmesser innen	Approx. Gewicht	Durchmesser aussen	Durchmesser innen	Approx. Gewicht
mm	mm	kg/m	mm	mm	kg/m
30	25	0.51	60	40	3.72
32	12	1.63	60	45	2.93
32	14	1.54	60	50	2.04
32	20	1.16	63	20	6.63
32	22	1.00	63	45	3.61
32	25	0.74	63	50	2.73
35	10	2.09	65	35	5.57
35	14	1.91	65	40	4.88
35	16	1.80	65	48	3.57
35	18	1.67	70	30	7.43
35	20	1.53	70	40	6.13
35	22	1.38	70	45	5.34
35	25	1.11	70	50	4.46
38	19	2.01	70	60	2.41
38	22	1.78	75	50	5.81
38	25	1.52	75	60	3.76
40	10	2.79	75	65	2.60
40	15	2.55	80	20	11.15
40	20	2.23	80	40	8.92
40	25	1.81	80	50	7.24
40	30	1.30	80	60	5.20
45	15	3.34	85	50	8.78
45	20	3.02	85	60	6.73
45	25	2.60	85	70	4.32
45	30	2.09	90	50	10.40
45	32	1.86	90	60	8.36
45	35	1.49	90	70	5.94
45	40	0.79	90	75	4.60
50	12	4.38	95	60	10.08
50	20	3.90	95	75	6.32
50	25	3.48	100	30	16.90
50	30	2.97	100	50	13.93
50	35	2.37	100	60	11.89
50	38	1.96	100	70	9.47
50	40	1.67	100	80	6.69
50	42	1.37	105	40	17.51
50	45	0.88	105	60	13.79
55	20	4.88	105	70	11.38
55	30	3.95	105	75	10.30
55	35	3.34	105	85	7.06
55	40	2.65	110	50	17.83
58	35	3.97	110	70	13.37
58	45	2.49	115	80	12.68
60	20	5.94	115	90	9.52
60	30	5.02	115	100	5.99
60	35	4.41			

Hinweis: Die Standard-Länge beträgt 1000 mm oder 2000 mm. Sonder-Baulängen auf Anfrage.